DIRECT COUPLING

PROFESSIONAL SMART

SERIES

Air technology system

COMPACK 2 - 3

ROTARY SCREW COMPRESSORS

FIXED SPEED - DIRECT DRIVE 1:1



COMPACK 2-3

COMPACK SERIES

COMPACK represents a real revolution in the sector, allowing the exploitation of the technical and technological standards of an industrial screw compressor, which was the exclusive prerogative of the piston compressors' markets until yesterday.

Thanks to the **Heating System**, which eliminates the problem of condensate generation, **COMPACK** can also be used in non-continuous use regimes. Thanks to the electronic control, **K-Tronic** is equipped with all the typical functions of larger-size machines, controlling the empty loading cycles automatically. Plus, with the same air output, it guarantees energy savings compared to the use of a piston compressor of the same flow rate.

Available version on **2,5 lt** tank, **90 lt** tank, **270 lt** tank and **Air Trolley** with single-phase and three-phase motor.





TECHNICAL SPECIFICATIONS OF COMPACK 2 SERIES COMPACK 2 SERIES Air Flow* Noise L.** Code Power Screw Tank Voltage Connection Dimensions Weight max 4 () **1**99 EAN н Volt/Hz/Ph dB[A] LxWxH(cm) **COMPACK 2 - grounded** 1850120507 2,7 3,6 ADAM 60/E 270 9,53 230/50/1 Ouick COMPACK 2 10 65 67x40x50 2,5 0,66 145 48 101,4 Connector 1850223507 4.1 ADAM S60/E 300 10.59 400/50/3 COMPACK 2 - trolley 1850120520 2,7 3,6 ADAM 60/E 270 9,53 230/50/1 COMPACK 2 Quick 2,5 0,66 10 145 65 68x55x92 52 115 1850223520 2.5L Trolley 400/50/3 Connector 3 4,1 ADAM \$60/E 300 10,59 **COMPACK 2 - on tank** 1850120508 2,7 3,6 ADAM 60/E 270 9,53 230/50/1 COMPACK 2 1/2 Gas 117x46x96 90 65 75 176 23.77 10 145 90 L 1850223508 3 4.1 ADAM \$60/E 300 10.59 400/50/3 COMPACK 2 - on tank with dryer 1850120509 2,7 3,6 ADAM 60/E 270 9,53 230/50/1 COMPACK 2 23,77 1/2 Gas 123x58x100 231 1850223509 90I + F ADAM S60/E 400/50/3 3 4,1 300 10,59 COMPACK 2 - on vertical tank 1850120513 3,6 ADAM 60/E 270 9,53 230/50/1 COMPACK 2 1/2 Gas 64x67x170 275 270 71,32 10 145 123 270L vertical 400/50/3 4,1 ADAM S60/E 300 10.59 1850223513 3

^{*} Performances measured according to ISO 1217, annex C. ** Noise level measured according to ISO 2151.

INTEGRATED AIR-END

COMPACK is made up of a state-of-theart pumping group, the most compact in the field, integrating the main components of a screw compressor (airend, separator tank, thermostatic and minimum pressure valve, intake valve). Innovative in the selection of materials, a heart of steel in an aluminum body.



- · Greatest energy efficiency
- Designed as a big compressor
- Cooling circuit
- Best performance in just a small amount of space
- Great compactness
- Electronic controller and load/unload system
- Super silenced
- Turnkey products with an aluminum case
- Fast and economical maintenance
- Anti-condensation system
- Constant and immediate air flow with no big tanks required





COMPACK 3 SERIES

TECHNICAL SPECIFICATIONS OF COMPACK 3 SERIES

| Code | Model | Power | | Screw | Tank | | Pressure max | | Air Flow* | | Noise L.** | Voltage | Connection | Dimensions W | | ight |
|----------------------|----------------------------|-------|------|-----------------|------|-------|-----------------|-----|----------------|--------|-------------|------------|--------------------|--------------|-----|-------|
| EAN | | | | | H | | bar | | ≋ □ | | ८ ३% | • | | 'T ↓H M | Ĺ | 2 |
| | | kW | Нр | | Lt | gal | bar | psi | ℓ/min | C.F.M. | dB[A] | Volt/Hz/Ph | BSP | LxWxH(cm) | Kg | lbs |
| COMPACK 3 - grounded | | | | | | | | | | | | | | | | |
| 1860323507 | СОМРАСК 3 | 4 | 5,4 | ADAM S60 CCW | 2,5 | 0,66 | 10 | 145 | 380 | 13,42 | 65 | 400/50/3 | Quick Connector | 67x40x50 | 48 | 101,4 |
| COMPACK 3 - trolley | | | | | | | | | | | | | | | | |
| 1860323514 | COMPACK 3 8L Trolley | 4 | 5,4 | ADAM S60 CCW | 8L | 2,11 | 10 | 145 | 380 | 13,42 | 65 | 400/50/3 | Quick Connector | 74x65x72 | 65 | 115 |
| COMPACK 3 - on tank | | | | | | | | | | | | | | | | |
| 1860323508 | COMPACK 3 90 L | 4 | 5,4 | ADAM S60 CCW | 90 | 23,77 | 10 | 145 | 380 | 13,42 | 65 | 400/50/3 | 1/2 Gas | 117x46x96 | 75 | 176 |
| COMPACK | 3 - on tank w | ith d | ryer | | | | | | | | | | | | | |
| 1860323509 | COMPACK 3 90L + E | 4 | 5,4 | ADAM S60 CCW | 90L | 23,77 | 10 | 145 | 380 | 13,42 | 65 | 400/50/3 | 1/2 Gas | 123x58x100 | 107 | 231 |
| COMPACK | 3 - on vertica | ltan | k | | | | | | | | | | | | | |
| 1860323513 | COMPACK 3 270L vertical | 4 | 5,4 | ADAM S60 CCW | 270 | 71,32 | 10 | 145 | 380 | 13,42 | 65 | 400/50/3 | 1/2 Gas | 64x67x170 | 123 | 275 |

^{*} Performances measured according to ISO 1217, annex C. ** Noise level measured according to ISO 2151.



KTC S.r.l Via Palazzon, 70 36051 Creazzo (Vicenza) Italy T +39 0444-551759 | F +39 0444- 1510104

www.ktc-air.com - info@ktc-air.com